



PAGEL[®]
SPEZIAL-BETON GMBH & CO KG



DECLARATION OF PERFORMANCE
according Annex III of the Regulation (EU) No 305/2011

V1/50 PAGEL Grout

No. 110050

1. Unique identification code of the product-type:
EN 1504-6: ZA.1
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
batch number: see packaging of the product
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Anchoring product
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
PAGEL SPEZIAL-BETON GMBH & CO. KG
Wolfsbankring 9
45355 Essen, Germany
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
not relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 2+ (for uses in buildings and civil engineering works)
System 4 (for uses subject to reaction to fire regulations)
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 1504-6, System 2+:
The notified body Qualitätsgemeinschaft Deutsche Bauchemie e.V., identification number 0921, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued:
Certificate of conformity of the factory production control 0921 - CPR - 2096
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
not relevant



PAGEL[®]
SPEZIAL-BETON GMBH & CO KG



9. Declared performance

Essential characteristics	Performance	Harmonised Technical specification
Pull-out	≤ 0,6 mm	EN 1504-6:2006
Chloride ion content	≤ 0,05 %	
Reaction to fire	A1	
Dangerous substances	NPD	

NPD "No Performance Determined"

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Daniel Schempershofe, Head of Laboratory
(name and function)

Essen, 01.07.2013
(place and date of issue)


.....
(signature)



PAGEL[®]
SPEZIAL-BETON GMBH & CO KG



DECLARATION OF PERFORMANCE
according Annex III of the Regulation (EU) No 305/2011

V1/50 PAGEL Grout

No. 110050

1. Unique identification code of the product-type:
EN 1504-3: ZA.1a
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
batch number: see packaging of the product
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Product for Structural and non structural repair for concrete
Applying mortar by hand (3.1)
Recasting with concrete (3.2)
Spraying concrete or mortar (3.3)
Structural strengthening by adding mortar or concrete (4.4)
Increasing cover to reinforcement with additional cementitious mortar or concrete (7.1)
Replacing contaminated concrete (7.2)

PCC Mortar for structural and non structural repair for concrete
(on the basis of hydraulic cement)
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
PAGEL SPEZIAL-BETON GMBH & CO. KG
Wolfsbankring 9
45355 Essen, Germany
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
not relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 2+ (for uses in buildings and civil engineering works)
System 4 (for uses subject to reaction to fire regulations)



7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 1504-3, System 2+:

The notified body Qualitätsgemeinschaft Deutsche Bauchemie e.V., identification number 0921, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued:

Certificate of conformity of the factory production control
0921 - CPR - 2034

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
not relevant

9. Declared performance

Essential characteristics	Performance	Harmonised Technical specification
Compressive strength	class R4	EN 1504-3:2005
Chloride ion content ¹⁾	≤ 0,05 %	
Adhesive bond	≥ 2,0 MPa	
Restrained shrinkage/expansion ²⁾	≥ 2,0 MPa	
Carbonation resistance ^{1) 3)}	NPD	
Elastic modulus	≥ 20 GPa	
Thermal compatibility	NPD	
Skid Resistance	NPD	
Coefficient of thermal expansion ⁴⁾	NPD	
Capillary absorption	NPD	
Reaction to fire	A1	
Dangerous substances	NPD	

¹⁾ Only relevant for repair of reinforced concrete

²⁾ Not required if thermal cycling is undertaken

³⁾ Not required if the repair product includes a surface protection system with proven protection against carbonation (EN 1504-2) or is a PC mortar

⁴⁾ Relevant to PC only

⁵⁾ Also possible A1, A2, B, C and D, whereby the last four classes in Germany for the time being need an approval from DIBt. The possible class F is not admitted in Germany. This class means in Germany „readily flammable“. In other European MS this class means „no performance determined“ (NPD)“ and is admitted with consideration of the valid regulation in the respective MS



PAGEL[®]
SPEZIAL-BETON GMBH & CO KG



10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Daniel Schempershofe, Head of Laboratory
(name and function)

Essen, 01.07.2013
(place and date of issue)

D. Schempershofe
.....
(signature)

V1[®]-GROUT

V1[®]/10 PAGEL GROUT (0-1 mm)
V1[®]/50 PAGEL GROUT (0-5 mm)
V1[®]/160 PAGEL GROUT (0-16 mm)

TEST CERTIFICATES AND SUPPORTING DOCUMENTS

- › Certificate of conformity DAfStb Directive (VeBMR) "Herstellung und Verwendung von zementgebundenem Vergussbeton und Vergussmörtel" (Manufacture and use of cement-bonded concrete grout and grout) (QDB)
- › Product acc. to DIN EN 1504-6 "Anchoring of reinforcing bars"
- › High frost-deicing salt resistance - Verification by CDF procedure
- › High sulfate resistance - Verification by testing acc. to DIN 19573 (**V1[®]/50** and **V1[®]/160**)
- › High resistance to chloride penetration - Verification by testing of the chloride migration coefficient (**V1[®]/50**)
- › Test acc. to DVGW Technical Rules, Work Sheets W 270 and W 347
- › Test acc. to DVGW Technical Rules, Work Sheet W 300 (**V1[®]/50**)
- › Verification of water penetration depth under pressure according to DIN 12390-8 (**V1[®]/160**)
- › Factory production control acc. to DIN EN 1504-3; table ZA. 1a for **V1[®]/50** and **V1[®]/160**
- › Factory production control acc. to DIN EN 1504-6
- › Company certification acc. to DIN EN ISO 9001:2015



PROPERTIES

- › High flowability
- › Controlled swelling with a frictional bond between concrete foundation and machine base plate
- › High early and final strength
- › Low modulus of elasticity in connection with a high bending tensile strength
- › Low w/c value
- › High frost-deicing salt resistance, impermeable to water and largely resistant to mineral oils and fuels
- › Pumpable and easy to process – even at low temperatures, using mono, mixing and feed pumps (ask for machine suitability)
- › Complies with the requirements of building material class A1 (non-combustible) as specified under decision 2000/605/EC of the European Commission dated September 26, 2000 (published in the official journal L258)

AREAS OF APPLICATION

- › Universal grout for precision machines of any kind
- › Turbines, generators, compressors, diesel engines and other power equipment exposed to high dynamic loads
- › Fixators
- › Steel and concrete columns
- › Prefabricated concrete parts and structural steelworks
- › Bridge bearings and bridge transition structures
- › Crane rails and radio telescopes, iron and steel works as well as mines
- › Paper plants, chemical plants and refineries
- › Pipe ducts in channel systems, sewage works and drinking water storage systems for gas and water pressure sealing

MOISTURE CLASSES BASED ON CONCRETE CORROSION FROM ALKALI-SILICIC ACID REACTIONS

Moisture class	WO	WF	WA	WS
GROUT	•	•	•	•

The aggregates in PAGEL®'s products comply with the requirements of alkali sensitivity class E1 from non-hazardous sources specified under DIN EN 12620.

EXPOSURE CLASS ALLOCATION ACC. TO: DIN EN 206-1 / DIN 1045-2

	XO	XC	XD	XS	XF	XA	XM
	1234	123	123	1234	1234	123*	123
V1®/10	•	••••	•••	•••	••••	••	••
V1®/50	•	••••	•••	•••	••••	•••	••
V1®/160	•	••••	•••	•••	••••	•••	••

* Classification of the sulfate resistance acc. to DIN 19573

Classification acc. to the DAfStb VeBMR directive:

	Flowability class	Slump flow class	Shrinkage class	Early strength class	Compressive strength class	
V1®/10	Categorisation	f2	-	SKVM II	A	C55/67
V1®/50	Categorisation	-	a3	SKVB I	A	C60/75
V1®/160	Categorisation	-	a2	SKVB I	A	C60/75



TECHNICAL DATA

TYPE			V1 [®] /10	V1 [®] /50	V1 [®] /160	
Grain size		mm	0-1	0-5	0-160	
Undergrouting height		mm	5-30	20-120	100-400	
Amount of water	max.	%	13	12	11	
Consumption (dry mortar) approx.		kg/m ³	2.000	2.000	2.100	
Fresh mortar raw density approx.		kg/m ³	2.250	2.300	2.300	
Processing time approx.	20 °C	min	90	90	90	
Slump flow (gutter)	5 min	mm	≥ 650	n. d.	n. d.	
	30 min	mm	≥ 550	n. d.	n. d.	
Measure of extension	5 min	mm	n. d.	≥ 700	≥ 600	
	30 min	mm	n. d.	≥ 620	≥ 520	
Swelling	24 h	Vol.-%	≥ 0,1	≥ 0,1	≥ 0,1	
Compressive strength*	1 d	N/mm ²	≥ 40	≥ 40	≥ 40	
	V1/10: 4x4x16 cm	7 d	N/mm ²	≥ 60	≥ 60	
	V1/50, V1/160: 15x15x15 cm	28 d	N/mm ²	≥ 80	≥ 75	≥ 75
		90 d	N/mm ²	≥ 90	≥ 90	≥ 90
Bending tensile strength**	1 d	N/mm ²	≥ 4	≥ 4	≥ 4	
	7 d	N/mm ²	≥ 6	≥ 6	≥ 6	
	28 d	N/mm ²	≥ 8	≥ 8	≥ 8	
	90 d	N/mm ²	≥ 10	≥ 10	≥ 10	
E-Module (static)	7 d	N/mm ²	≥ 30.000	≥ 30.000	≥ 30.000	
	28 d	N/mm ²	≥ 35.000	≥ 35.000	≥ 35.000	

* DIN EN 196-1-compliant mortar compressive strength testing;
DIN EN 12390-3-compliant concrete compressive strength testing

** DIN EN 12390-5-compliant bending tensile strength testing
n. d. = not determined

Note: All stated test values correspond to the DAfStb VeBMR directive.

Testing of fresh and solid mortars at 20 °C ± 2 °C, storage of the test specimen after 24 hours until the strength test in water at 20 °C ± 2 °C. Higher or lower temperatures result in deviating properties of fresh respectively solid mortars and test results. Depending on the temperature, the consistency can be adapted with a slight reduction of the mixing water.

Storage: 12 months. Cool, dry, free from frost. Unopened in its original container.
Delivery form: 25-kg bag, Euro pallet 1,000 kg
Hazard class: Non-hazardous material, observe information on packaging.
GISCODE: ZP1

PAGEL PRODUCT COMPOSITION:

Cement: acc. to DIN EN 197-1
Aggregate: acc. to DIN EN 12620
Additions: acc. to DIN EN 450, general building inspection approval (abZ),
DIN EN 13263 (fly ash, microsilica, etc.)
Admixtures: acc. to DIN EN 934-4

APPLICATION

SUBSTRATE PREPARATION:

Remove loose and unsound material such as cement slurry and dirt etc. using suitable methods, e.g. shot-blasting or similar until the underlying solid grain structure has been exposed. A sufficient average tear strength ($\geq 1.5 \text{ N/mm}^2$, KEW $\geq 1.0 \text{ N/mm}^2$) must be ensured.

Prewetting:

Prewet the concrete substrate to capillary saturation for approx. 6-24 hours.

Reinforcing steel:

Blast all rust off exposed reinforcement bars until the underlying metal has been exposed acc. to purity grade SA 2 ½ in accordance with DIN EN ISO 12944-4.

Non-iron metals:

Cement and cement-bound building materials may cause non-iron-metals in the transitional area of the contact surface (e.g. aluminium, copper, zinc) to loosen. Please contact us for technical advice.

FORMWORK:

Attach in such a way that it is leak-proof and robust. Seal on the concrete substrate. Use non-absorbent formwork.

Protruding grout:

Do not exceed the specified 50 mm when allowing grout to protrude and observe the structural specifications. When grouting dynamically stressed and pre-stressed base plates and machine foundations that are subject to high compression strengths at the edges, the grout should ideally be applied to be flush with the bearing plate, provided with a 45° edge using formwork or cut off flush with the bearing plate before it has set. This will prevent any stresses from becoming superimposed on one another and from becoming annihilated (observe static and structural specifications).

MIXING:

The dry mortar is supplied ready to use and only needs to be mixed with water. Fill the specified amount of water apart from a residual amount into a clean and suitable mixing device (e.g. compulsory mixer).

Add the dry mortar and mix for at least 3 minutes.

Add the remaining water and mix for at least another 2 minutes until it forms a homogeneous mass.

GROUTING:

The mixture must be poured from one side or corner only in one continuous pour. When grouting large areas, we recommend to pour starting in the centre of the foundation plate, using a funnel or filling hose. Cavities should be filled first (up to around just below the top edge) and then the machine plate or similar.

Temperature range: +5 °C to + 35 °C

Mixing water: Drinking water quality

FOLLOW-UP TREATMENT:

Exposed grout areas must be protected from premature water evaporation (from wind, draughts, direct exposure to sun, etc.) immediately on completion of the work for a period of 3-5 days.

Suitable curing methods:

Water spray, foil covers with jute sheets, thermofoils or moisture-retaining covering sheets,

01 EVAPORATION PROTECTION.

The technical data sheet must be observed when using **01** EVAPORATION PROTECTION.