

## **NEVOSAFETM**

Danterr proudly distributes the Nevosafe<sup>™</sup> rebar capping system, the industry benchmark in construction site safety. Crafted with a heavy-duty steel core, Nevosafe<sup>™</sup> promises exceptional impalement protection, aligning with strict safety protocols. This safety strip affixes in seconds, enhancing any worksite with immediate, visible safety measures. Designed for durability and multiple uses, Nevosafe<sup>™</sup> not only improves safety but also offers long-term economic value.

## **KEY BENEFITS**

- Industrial-Grade Protection: Features an industrialgrade steel core that delivers superior resistance to impalement.
- Rapid Deployment: Can be installed swiftly, with each strip taking less than 7 seconds to secure.
- Reusable Efficiency: Offers premium reuse potential across various sites, providing cost-effectiveness.
- **Empirical Certification**: Complies with EMPA TEST CERTIFICATE 460' 353/2, ensuring reliability.
- Innovative Design: The elongated design permits work on both sides of the rebar, maximizing site productivity.
- High Visibility: Brightly colored for increased visibility, reducing the risk of worksite accidents.
- **Weight Resilience:** Tested to prevent impalement from falls, supporting an adult's weight of up to 100kg from a height of 3 meters.
- Versatile Application: Suitable for use in diverse construction environments, including highrise levels.



## **TECHNICAL DATA**

Per EMPA Test Certificate 460′ 353/2 dated May 9, 2012, the Nevosafe<sup>™</sup> safety strip effectively prevents impalement hazards on construction sites. Tested on common rebar sizes under practical conditions, the strip withstood a 3-meter drop test with a 100kg sandbag, ensuring no penetration occurred. Passing rigorous safety tests, Nevosafe<sup>™</sup> is verified as ready for immediate deployment to safeguard construction workers from fall-related impalement risks.

| ITEM NUMBER | FOR IRON Ømm | LENGTH (m) | PCS/BUNDLE | PCS/PALLET |
|-------------|--------------|------------|------------|------------|
| 104094      | 8-40         | 1          | 6          | 252        |

